

PANSEAL

Part A
Resin

SDS Revised March 2018
Complies with OSHA HCS Standards
1.

Safety Data Sheet (Complies with OSHA HCS)

Section 1: Identification

Product identifier	2000 Series Part A Coating and Lining (All Colors)
Other means of identification	PANSEAL, 2000PG, 2000PC, 2000PB
Recommended use	Not available
Recommended restrictions	None known
Manufacturer/Importer/Supplier/ Company Name:	Distributor information Dynesic Technologies, Inc. 15230 Surveyor Blvd., Addison, TX 75001 Phone: 972-692-0962
After hours telephone number	Phone: 972-692-0962
Website	www.dynesic.com
Email	sphillips@dynesic.com
Emergency 24 hour telephone	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887
Operation hours information	7:00 a.m. to 7:00 p.m.

Section 2: Hazard(s) Identification

Physical hazards	Not classified
Health hazards	
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Environmental hazards	Not classified
OSHA defined hazards	Not classified
Label elements	



Signal word	Warning
Hazard statement	Causes eye irritation. Causes skin irritation.
Prevention	Wear protective gloves. Wear eye/face protection. Wash thoroughly after handling.
Response	Specific treatment see Section 4 of this SDS. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	Store in accordance with local/regional/national regulations.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known
Supplemental information	Not applicable

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
2.

Section 3: Composition/Information on Ingredients

Mixtures

Chemical name	CAS number	%
BISPHENOL A-(EPICHLORHYDRIN) EPOXY RESIN	25068-38-6	35 - 65
2,3 EPOXYPROPYL NEODECANOATE	26761-45-5	2 - 12
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	28064-14-4	1 - 6
CARBON BLACK	1333-86-4	0 - 1

* Other components below reportable levels 50.5

Section 4: First Aid Measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General Information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5: Fire-Fighting Measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
3.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Section 7: Section 7: Handling And Storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Section 8: Exposure Controls/Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
CARBON BLACK (CAS 1333-86-4)	PEL	3.5 mg/m ³	
US. ACGIH Threshold Limit Values CARBON BLACK (CAS 1333-86-4)	TWA	3.5 mg/m ³	Inhalable fraction
US. NIOSH: Pocket Guide to Chemical Hazards CARBON BLACK (CAS 1333-86-4)	TWA	0.1 mg/m ³	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

Wear suitable protective clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
4.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9: Physical and Chemical Properties

Appearance	Not available
Physical state	Liquid
Form	Liquid
Color	Golden to Light Amber
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting point/freezing point	Not available
Initial boiling point/boiling range	212 °F (100 °C) estimated
Flash point	482.0 °F (250.0 °C) estimated
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available
Flammability limit upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	0.01 hPa estimated
Vapor density	Not available
Relative density	Not available
Solubility(ies) Solubility (water)	Partial
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Flammability Class	Combustible IIIB estimated

Section 10: Stability and Reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
5.

Section 11: Toxicological Information

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
Information on toxicological effects	
Acute toxicity	Not available
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.
IARC Monographs. Overall Evaluation of Carcinogenicity	
CARBON BLACK (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
	Not listed
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified
Specific target organ toxicity - repeated exposure	Not classified
Aspiration hazard	Not available
Chronic effects	Prolonged inhalation may be harmful.

Section 12: Ecological Information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms.

Product	Species	Test Results
----------------	----------------	---------------------

2000 Series Part A Coating and Lining (All Colors) (CAS Mixture)

Crustacea EC50	Daphnia	6.6372 mg/l, 48 hours estimated
Fish LC50	Fish	3.6873 mg/l, 96 hours estimated

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
6.

Components	Species	Test Results
BISPHENOL A-(EPICHLORHYDRIN) EPOXY RESIN (CAS 25068-38-6)		
Crustacea EC50	Daphnia magna	2.7 mg/l, 48 hours
Fish LC50	Salmo gairdneri (new name Oncorhynchus mykiss)	1.5 mg/l, 96 hours
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)		
Acute		
Fish LC50	Fish	1 - 10 mg/l
* <i>Estimates for product may be based on additional component data not shown</i>		
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

Section 13: Disposal Considerations

Disposal instructions

When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Section 14: Transportation Information

DOT Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available

Section 15: Regulatory information

US federal regulations

All components are on the U.S. EPA

TSCA Inventory List. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
7.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed

SARA 311/312 Hazardous chemical

Yes

SARA 313 (TRI reporting)

Not regulated

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

Safe Drinking Water Act (SDWA)

Not regulated

US state regulations

US. Massachusetts RTK - Substance List

CARBON BLACK (CAS 1333-86-4)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated

US. Pennsylvania RTK - Hazardous Substances

Not regulated

US. Rhode Island RTK

Not regulated

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4) Listed: February 21, 2003

International Inventories

Country(s) or region/Inventory name	On inventory (yes/no)*
Australia Australian Inventory of Chemical Substances (AICS)	Yes
Canada Domestic Substances List (DSL)	Yes
Canada Non-Domestic Substances List (NDSL)	No
China Inventory of Existing Chemical Substances in China (IECSC)	No
Europe European Inventory of Existing Commercial Chemical Substances	Yes
Europe European List of Notified Chemical Substances (ELINCS)	No
Japan Inventory of Existing and New Chemical Substances (ENCS)	No
Korea Existing Chemicals List (ECL)	No
New Zealand New Zealand Inventory	No
Philippines Philippine Inventory of Chemicals and Chemical Substances	No
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

PANSEAL

Part A
Resin

SDS

Complies with OSHA HCS Standards
8.

Section 16: Other information

Issue date 03-30-2015
Version # 01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



15230 Surveyor Blvd., Addison, TX 75001
Phone: 972-692-0962, www.dynesic.com