

TRANSFORMING AIR PURIFICATION

For More Information Contact
Proac Corporation
Toll Free: 877-255-0558
Email: info@proaccorp.com
Website: www.proaccorp.com

750+
wall mount



Greentech 750+ wall mount
Active Air Purifier with PCO Technology

We measure success in microns.

Applications:

Workshops • Offices • Schools
Day Care Facilities • Nursing Homes • Nail
Salons • Veterinary Clinics • Motor Coaches
Public Restrooms

- Active Air Purification
- No Ductwork Required
- Easily Mounts to Wall
- 24/7 Odor and Particulate Reduction
- Replaceable PCO Cell and MERV filter +

Benefits of Greentech's 750+ Wall Mount



Continuous Purification



Reduces Odors



Mounts to Save Space



Sized for Multiple Locations



Wide List of Applications

Active Oxidation Improves Air Quality



Providing continuous air purification, this permanently mounted unit is perfect for spaces without HVAC duct access. Greentech's 750+ Wall Mount features the same active air purification technology developed and used by NASA.



AOPs are propelled out into your space to hunt down particulates, even the very small ones. At the same time, negative ions go out and charge particles such as dust, pollen and pet dander, causing them to drop out of your breathing space.



Photocatalytic oxidation (PCO) technology uses energy to activate a catalyst, turning moisture into products that continuously clean your space.



With a reactive surface area more than 16x greater than the competition, Greentech's 750+ Wall Mount continuously purifies your space. The result is the reduction of allergens from pets, pollen, and smoke, as well as odors from mold, mildew, and more.

Features and Specifications

UNIT

- Models: Greentech SIREN 750+ Wall Mount 1X5789
Greentech 750+ Wall Mount NO3 (no ozone) 1X5821
- Dimensions: 11.92" H x 9.72" W x 3.64" D
- Metric: 303mm H x 247mm W x 93mm D
- Weight: 3.3lbs (1.5kg)
- Materials: Powder Coated Aluminum
- Unit Warranty: 2 Year Manufacturer's Warranty

PERFORMANCE

- Airflow: 70 CFM
- Optional Ozone Output: < 0.05 ppm
- Coverage: up to 750 ft²

POWER

- Input Voltage: 24VDC
- Operating Voltage 24VDC
- Supply Power: 120-240VAC | 17W
- Operating Power: 24VDC | .67A

TECHNOLOGIES

- PCO: Photocatalytic Oxidation
- Bipolar Ionization Module (BPI)
- Activated Oxygen (Ozone) - Optional

To Use This Product Correctly

- 1 Read All Instructions Carefully in User Manual Before Operating Purifier.